

PRODUCT No. 6317

Fluid for cleaning tables – STANDARD C – 160 l



(Illustrative photograph)

Technical data

Characteristics	Perfect grease removal
Barrel capacity	160 l
Flash point	63°C
Density at 15°C	790 kg/m ³
Viscosity at 25°C	1,23 mm ² /s
Flammable class	III.

Attributes

- C-Standard fluid is a mixture of petroleum halogenated hydrocarbons free of halogens.
- Used to bleach free crease removal and cleaning of components when cold in spray, dip or manual machinery.
- Ideal for repair shops, maintenances and industrial operations.
- For perfect degreasing in repairs, painting and galvanizing operations, for cleaning parts and devices.
- Excellent cleaning ability, efficiency for most oils, greases, fats and waxes, suitable evaporation, does not damage the surface, does not corrode materials, ideal for steel, aluminium, zinc, copper and titanium, high saturation, dries without mapping, aroma content up to 0,03% hm, minimal load for air environment.
- All types of fluids for cleaning tables are odorless.
- Long-term usability (standardly 12 – 36 months).

Product purpose

- Very effective means for degreasing parts in car repair shops, electrodes and paint shops. Suitable especially for washing electric tools, electrodes and components designed for further surface treatment in paint shops and galvanization operations.